



ROTATE TWO TURNS COUNTER  
CLOCKWISE TO RELEASE THE  
TURN BUCKLE PRIOR TO TIGHTENING

TURN BUCKLES ROTATE 90 DEG. INTO  
THEIR CLAMPING POSITION AS  
MOUNTING SCREWS TIGHTEN.  
DO NOT OVER-TORQUE!



These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS				
VOLTS:		125V		
AMPS:		3A		
SCCR:		0.2kA		
NEMA/UL   EN 60529:		4, 12   IP65		
PANEL THICKNESS:		5.0mm max		
MOUNTING SCREW TORQUE:		0.8N-m		
TERMINAL BLOCK TORQUE:		0.5N-m		
INCOMING POWER WIRE SIZE:		0.25 - 2.5 sq mm / 24-12AWG		
WIRE STRIP LENGTH:		7 - 8 mm		
DRAWN BY	DG	MENCOM CORPORATION  TITLE:  GFI; RJ45; R; LP3		
DRAWN DATE	08/03/2020			
CHECKED BY	DCG			
CHECK DATE	08/03/2020			
COMMENTS:		SIZE	DWG. NO.	REV
		B	LP3-GF-RJ45-R	B
		SCALE: 1:2	WEIGHT:	SHEET 1 OF 1

HOUSING MATERIALS	
BODY:	NICKEL PLATED ZINC
GASKETS:	PUR FIPG
FRONT COVER:	POLYCARBONATE
LATCH & LOCK:	PBT
BACK COVER:	POLYPROPYLENE

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES AND [MM]	
MATERIAL	
FINISH	
DO NOT SCALE DRAWING	

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.