PIN #	COLOR
1	RED w/WHITE
2	RED
3	GREEN / YELLOW
4	RED w/YELLOW
5	RED w/BLACK
6	RED w/BLUE

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	7/27/2005	



P/N	L	STD?
MAC-6MFP-1M	40" [1m]	YES
MAC-6MFP-2M	79" [2m]	YES
MAC-6MFP-3M	118" [3m]	YES
MAC-6MFP-4M	157" [4m]	YES
MAC-6MFP-5M	197" [5m]	YES
MAC-6MFP-6M	236" [6m]	YES
MAC-6MFP-8M	315" [8m]	NO
MAC-6MFP-10M	393" [10m]	YES
MAC-6MFP-15M	591" [15m]	YES
MAC-6MFP-20M	787" [20m]	NO
MAC-6MFP-30M	1181" [30m]	NO
MAC-6MFP-50M	1968" [50m]	NO

PARTS LISTED AS NOT BEING STANDARD
MAY REQUIRE MINIMUM ORDERS

MATERIALS	
BODY:	YELLOW PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	22/6 AWM 2661 YELLOW PVC JACKET
COUPLING:	NICKEL PLATED BRASS
INSERT:	POLYAMIDE
O-RING:	BUNA N

APPROVALS:	
US	UL RECOGNIZED
CANADA	C-UL RECOGNIZED

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS	300V
AMPS	4A
TEMP	105°C

SPECIFICATIONS

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

	NAME
DRAWN	DWM
CHECKED	
ENG APPR.	
MFG APPR.	
Q.A.	

COMMENTS:

MENCOM CORPORATION

TITLE:

SIZE	DWG. NO.	REV
B	MAC-6MFP-ZZ	A

SCALE: 3:2 | WEIGHT: | SHEET 1 OF 1